



of Excellence

1.800.381.5335

sales@marsmetal.com

www.marsmetal.com



Scan with your mobile/smart
phone barcode reader.

LEAD ROOFING

Over 70 tons of sheet lead in stock in various sizes are available for immediate shipping!



Mars Metal provides sheet lead conforming to Federal QQ-L-201F and QQ-L-171E (and ASTM B-29 and B-749). Made from 98% recyclable material. Sheet lead is the most malleable of common metals and can be easily shaped, formed, bend and cut to suit a variety of applications, including lead roofing and flashing.

FEATURES & BENEFITS

Longevity

- Lead lasts an average of more than three times longer than other roofing and flashing products.
- Lead is resistant to corrosion from the atmosphere, salt water and most natural chemicals.
- Lead is recyclable and can be re-used.

Flexibility

- Sheet lead can be tightly dressed around junctions and penetrations and is the only material that can protect these areas from water penetration.
- Lead is able to cope with wide ranging temperature fluctuations, and its malleability ensures no cracking and UV degradation.

Installation

- Sheet lead installation is not impacted by damp or cold weather conditions.

IN STOCK SIZES/THICKNESSES

Lead Thickness Chart

Normal Sheet lead sizes and weights

THICKNESS FRACTIONS	DECIMAL EQUIVALENT	mm EQUIVALENT	LBS.PER SQ.FT (approximately)
1/32"	0.0313"	0.795mm	2#
1/16"	0.625"	1.5875mm	4#
1/8"	0.125"	3.1750mm	8#
1/4"	0.250"	6.3500mm	16#

Please note: Custom thicknesses available from .0156" to 2". Cut sizes available.

**Federal Specification QQ-L-201f and QQ-L-171 available.
ASTM Specification ASTM B29-03 and ASTM B749 available.**

We stock 1/32", 1/16" and 1/8" sheet lead in 8 foot and 10 foot rolls. 1/32", 1/16" and 1/8" lead strips are available in 2" X 8 foot and 2" X 10 foot.



Speciality Casting Division

Mars Metal



Of Excellence

1.800.381.5335
sales@marsmetal.com
www.marsmetal.com



Scan with your mobile/smart phone barcode reader.